



Ultra1Plus™ SAE 15W-40 Conventional motor oil API SL

Product description

Ultra1Plus™ SAE 15W-40 Conventional motor oil, API SL is a gasoline engine oil blended with group II paraffinic base stock and premium additive package.

This oil exhibits good anti-wear, antioxidant, anti-foaming, detergent, and dispersant characteristics. This oil exceeds the performance requirements of API SL.

Product features & benefits

- Helps prevent deposits and sludge buildup to enable long engine life.
- Provides overall lubrication and wear protection performance for many driving styles.
- Provides better control of emissions.
- Delivers outstanding performance during the maximum oil change interval recommended in a vehicle's owner's manual.
- Reduces the consumption of lubricant by evaporation at high temperatures.

Product code

Presentation	SKU	UPC
5 Gallon Pail	UC1540SLP	810050651189
55 Gallon Drum	UC1540SLD	810050651172
265 Gallon Tote	UC1540SLT	810050651165

Exceeds performance requirements

API SL

Typical properties

SAE J300 Viscosity grade	15W-40
Appearance	Amber, transparent liquid
Viscosity @ 40°C, cSt, ASTM D445	105.1
Viscosity @ 100°C, cSt, ASTM D445	14.0
Viscosity index, ASTM D2270	135
Flash point, °C, ASTM D92	220
Pour point, °C, ASTM D97	-32



Revised: 06/21/2021