

U1P-Bike - 4T Synthetic Blend Motor Oil

SAE 10W-40 API SL, JASO MA2

Motorcycle – ATV | United States

Product Description

Ultra 100% synthetic 4-Stroke engine oil. Top performance formula that meets and exceeds the highest industry standard JASO MA2 API SL specifications. Top technology 100 % synthetic base-stock with precisely balanced Ultra high-performance additive package. Allow maximum power delivery by reducing internal friction for exceptional wear protection, Increasing engine life for on-road, off-road, street or motorsports. Proven at extreme temperature racing conditions, speed, and endurance.



Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SL ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- For liquid cooled or air-cooled engines. Improves thermal stability and fuel efficiency.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer’s oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



Product Code

Presentation	SKU	Manufacture ID	UPC
QT	USB10404TSLMA2L	UL401	810050651929
1 US Gallon	USB10404TSLMA2G	UL401	810050651912
5 Gallon Pail	USB10404TSLMA2P	UL401	810050651905
55 Gallon Drum	USB10404TSLMA2D	UL401	810050651899
265 Gallon Tote	USB10404TSLMA2T	UL401	810050651882



This product meets or exceeds the requirements of:

API SL

JASO MA

JASO MA2

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	97.25
Viscosity @ 100°C, cSt, ASTM D445	15.5
Viscosity index, ASTM D2270	155
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	23,000@-30°C
Pour point, °C, ASTM D97	-40
Flash point, °C, ASTM D92	215



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023