

U1P-Drive - Synthetic Blend Motor Oil

SAE 10W-30 API SP, ILSAC GF-6A

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 10W-30 Synthetic Blend Motor Oil, API SP, ILSAC GF-6A is a high-performance multigrade motor oil formulated for gasoline engines, combining full synthetic base stocks and Mineral base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines in both normal and extreme operating conditions.

U1P-DRIVE SAE 10W-30 Synthetic Blend Motor Oil, API SP, ILSAC GF-6A exceeds the performance requirements of API SP, ILSAC GF-6A quality certifications. Delivers engine protection and cleanliness. Recommended for on-road and off-road use, light duty, and heavy duty. Creates a strong lubricant film in both cold and hot weather. Excellent for American, European, and Asian gasoline engines that require API SP quality motor oil and previous certifications. Substitutes older API (SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even in extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
QT	USB1030SPGF6AL	UL203	810111110686
1 US Gallon	USB1030SNGF5G	UL203	810050650656
1 JUG (5 QTS)	USB1030SPGF6AJ	UL203	810050658447
5 Gallon Pail	USB1030SPGF6AP	UL203	810050650649
55 Gallon Drum	USB1030SPGF6AD	UL203	810050650632
265 Gallon Tote	USB1030SPGF6AT	UL203	810050650625



This product meets or exceeds the requirements of:

API SP, API SN Plus with Resource Conserving, API SN, API SM, API SL, API SJ

ILSAC GF-5

ILSAC GF-6A

GM6094M

Chrysler MS6395



Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	70.7
Viscosity @ 100°C, cSt, ASTM D445	10.9
Viscosity index, ASTM D2270	145
CCS Apparent Viscosity, cP, ASTM D5293	5,000@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	9,800@-30°C
Pour point, °C, ASTM D97	-40
Flash point, °C, ASTM D92	215



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 04/04/2025