

U1P-Drive - Synthetic Blend Motor Oil

SAE 20W-50 API SP

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 20W-50 Synthetic Blend Motor Oil, API SP is a high-performance multigrade motor oil formulated for gasoline engines, combining full synthetic base stocks and Mineral base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines in both normal and extreme operating conditions.

U1P-DRIVE SAE 20W-50 Synthetic Blend Motor Oil, API SP exceeds the performance requirements of API SP quality certification. Delivers engine protection and cleanliness. Recommended for on-road and off-road use, light duty, and heavy duty. Creates a strong lubricant film in both cold and hot weather. Excellent for American, European, and Asian gasoline engines that require API SP quality motor oil and previous certifications. Substitutes older API (SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even in extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	USB2050SPL	UL205	810050650786
1 US Gallon	USB2050SPG	UL205	810050650779
5 Gallon Pail	USB2050SPP	UL205	810050650762
55 Gallon Drum	USB2050SPD	UL205	810050650755
265 Gallon Tote	USB2050SPT	UL205	810050650748



This product meets or exceeds the requirements of:

_____	API SP
_____	API SN
_____	API SM
_____	API SL
_____	API SJ



Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	160.55
Viscosity @ 100°C, cSt, ASTM D445	18.5
Viscosity index, ASTM D2270	130
CCS Apparent Viscosity, cP, ASTM D5293	5,900@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	15,600@-20°C
Pour point, °C, ASTM D97	-30
Flash point, °C, ASTM D92	220



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023