

**U1P-Duty - Synthetic Blend Motor Oil**

**SAE 25W-60 API CH-4/SJ**

Heavy-Duty | United States

**Product Description**

U1P-DUTY SAE 25W-60 Synthetic Blend Heavy-Duty Motor Oil, API CH-4/SJ (Green) is a parasyntetic crankcase lubricant for use in modern diesel engines. Formulated with a blend of synthetic and conventional base oils as well as an Ultra-premium quality additive package, this oil exhibits good detergent, dispersant, anti-wear, anti-corrosion, antioxidant, and anti-foaming properties.



**Features and Benefits**

- Improves engine power and performance.
- Reduces oil leaks in engines with more than 65.000 miles.
- Reduces excessive oil consumption due to higher viscosity.
- Protects internal engine parts, with high mileage from wear.
- Reduces the accumulation of sludge and the formation of harmful deposits.



**Product Code**

Presentation	SKU	Manufacture ID	UPC
QT	USB2560CH4SJL	UL209	810050651028
1 US Gallon	USB2560CH4SJG	UL209	810050651011
5 Gallon Pail	USB2560CH4SJP	UL209	810050650823
55 Gallon Drum	USB2560CH4SJD	UL209	810050650816
265 Gallon Tote	USB2560CH4SJT	UL209	810050650809



**This product meets or exceeds the requirements of:**

API CH-4, CF-4, CF-2, CF  
API SJ, SG, SF

**Properties and Specifications\***

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	252.15
Viscosity @ 100°C, cSt, ASTM D445	24.0
Viscosity index, ASTM D2270	120
CCS Apparent Viscosity, cP, ASTM D5293	6,800@-10°C
Pour point, °C, ASTM D97	-20
Flash point, °C, ASTM D92	235
Total Base Number, mg KOH/g, ASTM D2896	9

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



Revised: 07/14/2025