

U1P-Duty – Conventional Transmission Fluid

SAE 10W Drivetrain Torque, TO-4

Heavy-Duty | United States

Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, **Ultra1Plus™ SAE 10W Hydraulic Oil, TO-4** exhibits good oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures.

Features and Benefits

- High shear stability.
- Good foam resistance.
- Superior High- and Low-Temperature performance.
- Compatible with a wide variety of seals and friction materials.
- It has excellent oxidation resistance.

This product meets or exceeds the requirements of:

CAT TO-2 & TO-4

Allison C-4, API MT-1, CF-2, CF

Komatsu KES 07.868.1

ZF TE-ML-03C, ZF TE-ML-07F

Vickers 35VQ25 Pumps

Technical Information*

Parameter	Test	10W
Appearance	-	Yellow, Transparent, Liquid
Viscosity @ 40°C, cSt	ASTM D445	43.25
Viscosity @ 100°C, cSt	ASTM D445	6.92
Viscosity index	ASTM D2270	105
Pour point, °C (°F)	ASTM D97	-36 (-32.8)
Flash point, °C (°F)	ASTM D92	200 (392)

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023

