

## U1P-Gear - Full Synthetic Gear Oil

# SAE 75W-140, API GL-5

Transmission | United States

### Product Description

U1P-GEAR SAE 75W-140 Full Synthetic Gear Oil, API GL-5 is formulated with synthetic base oils and specialty performance additives to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions. Specialty anti-scuffing additives and friction modifiers provide advanced protection and lubricity in extreme pressure conditions. Additionally, U1P-GEAR SAE 75W-140 Synthetic Limited Slip Gear Oil, API GL-5, MT-1 is highly shear stable while also resisting rust, oxidation, foaming, and varnish.

U1P-GEAR SAE 75W-140 Synthetic Gear Oil, API GL-5 is designed for use in all seasons and exceeds the year-round, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5 and MT-1. API Category GL-5 designates the type of service characteristic of gears, particularly hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions. Lubricants meeting API MT-1 provide protection against the combination of thermal degradation, component wear, and oil seal deterioration which is not provided by lubricants meeting only the requirements of API GL-5. These oils also meet or exceed the performance requirements of the following industry and OEM specifications: API GL-5, API MT-1, Mack GO-J Plus (75W-140), SAE J2360, and Meritor O76-E.

### Features and Benefits

- Strong and stable lubrication film for minimum wear.
- Extended gear and bearing life due to minimal deposits.
- Exceptional thermal stability and resistance to high-temperature oxidation.
- Reduced maintenance costs by extending the life of seals and other components.
- Increased load-carrying capability.
- Adequate lubrication at extremely low and high temperatures.
- Minimum leakage and reduced contamination.
- With Limited Slip Differential additive package.



**Product Code**

Presentation	SKU	Manufacture ID	UPC
QT	UFS75140GL5L	UL705	810050654265
5 Gallon Pail	UFS75140GL5P	UL705	810050654241
55 Gallon Drum	UFS75140GL5D	UL705	810050654234
265 Gallon Tote	UFS75140GL5T	UL705	810050654227



**This product meets or exceeds the requirements of:**

API GL-5

API MT-1

Mack GO-J Plus (75W-140)

Meritor O76-E

**Properties and Specifications\***

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	176.7
Viscosity @ 100°C, cSt, ASTM D445	25.0
Viscosity index, ASTM D2270	175
Pour point, °C, ASTM D97	-48
Flash point, °C, ASTM D92	205

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.